Artikel-Nr.: 0409079

Bez.: SMA-Winkelstecker, Crimpausführung, RG 58/U, vergoldet

	Impedance		50Ω			-	different menter of the	PMN wasun MA saughtrakung Atlano	18,5	THE PARTY OF THE PROPERTY OF THE PARTY OF TH				
***************************************	Frequency range	0 to 18 GHz				2000	5	77777	72			*		
	Voltage rating	RG-55.58.141.142.223.303: 500 volts peak RG-122.174.188.316.375: 375 volts peak			Hex .							1	1	TI
(s	VSWR traight connectors)	RG-55 group:1.15+0.011(GHz) RG-178 group:1.20+0.251(GHz)					AT THE			1111 14		0 26	>	MUNO.
C	ontact resistance	Center: 2.0 mi Braid to body	iliohms Body:2.0 y:0.5 miliohms	miliohms		1/4-30	_(		74	Tamanago manago mateo a		1		¥ V
Ins	sulation resistance	5000 MHz								888		1		
	Insertion loss	0.03√f(GHz)	dB max							888	N	1.0		
7	Nut	Brass	Gold				T		T I	×××			-	
7 6	Nut Gasket	Brass Rubber	Gold Red						Millian	Ø 3, 2	X	1		
7 6 5			445 - 1 (484 - 1 486 ) 1 (464 ) (47 (49) (49 (49) (49 (49) 48			•		A STATE OF THE STA		Ø 3. 2	5		- FN FFI	PRITE
5	Gasket	Rubber	Red			7					5	1:CRIMP HEX C		RRULE SIZE: .
5 4	Gasket Ferrule	Rubber Brass	Red Gold								5 R	HEX C	RIMP S	
	Gasket Ferrule Shell	Rubber Brass Brass	Red Gold Gold			si					5 R	HEX C	RIMP S	
5 4 3	Gasket Ferrule Shell Insulator	Rubber Brass Brass Teflon	Red Gold Gold White			si		Ø 5.			5 R	HEX C	RIMP S	

## www.bkl-electronic.de

Die Angaben auf unseren Datenblättern erfolgen nach bestem Wissen. Sie sind nur ein unverbindlicher Hinweis und dienen als Anhaltspunkt für Planungen. Sie befreien den Anwender nicht von eigener Prüfung der von uns gelieferten Produkte auf ihre Eignung für die beabsichtigten Anwendungszwecke. Änderungen behalten wir uns vor, falls neue Erkenntnisse dies erforderlich machen. Ausführungen können variieren. Sollten Sie ein Muster benötigen kontaktieren Sie uns bitte.

BKL-Electronic Kreimendahl GmbH · Märkenstück 14 · 58509 Lüdenscheid Tel: +49 (0)2351-3621-0 · Fax: +49 (0)2351-3621-29 · info@bkl-electronic.de

